



SKU: PICS-854

UPC: 0783669232738

Features & Benefits:

Description: Aluminum Insulated Service Entrance Sleeve, Dual Rated, Main Conductor Size 4/0 Compact or 3/0, Tap Range 2 Sol - 4, Black Color Code, Die Index K-840

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Flared End	No
ILSCOs Die Index Number	K-840

Dimensions

Height (IN)	1.01
Height BX (IN)	3.75
Height (mm)	25.654
Length (IN)	5.5
Length (mm)	139.7
Weight (LB)	0.175291057242799
Weight BX (LB)	6.395
Width (IN)	1.01
Width BX (IN)	6.5
Width (mm)	25.654

Material and Finish

Conductor Material	Aluminum
Connector Finish	NA
Insulation	Nylon
Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366923273

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

ANSI Specification	ANSI C119.4
CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
RUS Listed	Yes
UL Control Number	NA
UL File Number	NA

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Black
Color Code	Black
Color Code Secondary	Orange

Conductor Ranges

Conductor Range ACSR (Secondary, tap, load)	3/0 ACSR
Conductor Range ACSR (primary, run, main, line)	4 ACSR
Conductor Range AL Solid (Secondary, tap, load)	2 Sol - 4 Sol
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str COMPACT or 3/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 4 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	2 Sol - 4 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str COMPACT or 3/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 4 Str
Conductor Range AL Solid (Primary, run, main, line)	2 Sol - 4 Sol