

NEER Zinc Bushed Conduit Nipples

CNN: Zinc

Applications

- Use through knockout to connect box to conduit coupling.
- Use with a locknut to connect two boxes side by side or back to back.
- Use with a locknut to connect fixture housings to continuous runs.

Features

- Male hub threads — NPS.
- Available with insulated throat.

Material/Finish

- Zinc die cast

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14814
- CSA Standard: C22.2 No. 18
- CSA Certified: 065178
- NEMA: FB-1



CNI-100

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters	
		Maximum Diameter	Body Length
Without Insulated Throat			
1/2	CNN-100	0.94/23.9	0.59/15.0
3/4	CNN-200	1.19/30.2	0.72/18.3
1	CNN-300	1.38/35.1	0.85/21.6
1-1/4	CNN-400	1.74/44.2	0.87/22.1
1-1/2	CNN-500	2.12/53.8	0.90/22.9
2	CNN-600	2.55/64.8	1.15/29.2
2-1/2	CNN-700	3.21/81.5	1.43/36.3
3	CNN-800	3.80/96.5	1.43/36.3
3-1/2	CNN-900	4.27/108.5	1.43/36.3
4	CNN-1000	4.79/121.7	1.43/36.3

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters	
		Maximum Diameter	Body Length
With Insulated Throat			
1/2	CNI-100	0.94/23.9	0.67/17.0
3/4	CNI-200	1.19/30.2	0.80/20.3
1	CNI-300	1.38/35.1	0.93/23.6
1-1/4	CNI-400	1.74/44.2	0.95/24.1
1-1/2	CNI-500	2.12/53.8	0.98/24.9
2	CNI-600	2.55/64.8	1.23/31.2

COMMERCIAL PRODUCTS: RIGID AND IMC FITTINGS

Commercial Products