



Catalog No. TF30R

Description: GE 30A GD ACD F PULLER 3HP STEEL N3R

UPC No 783164209884

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Puller Type AC Disconnect

30 Amp , Fusible General Duty - Steel Disconnect.



Representative Image

Descriptors

Category	Puller Type AC Disconnect
GO Schedule	RX

Specifications

Voltage	240 Vac
Amperage	30 A
Fusing	Fusible
Enclosure	NEMA Type 3R
Wire Range (Cu/Al)	14-3 Cu/Al
GSA Compliance	No

Classifications

UL Listed	CULUS Listed
-----------	--------------

Dimensions

Height	7.5 in
Depth	2.5 in
Width	5.2 in
Weight	2.216 lbs

Publications

Title	Publication No.	Publication Type
Fusible and Non-Fusible AC Disconnects Rev. F. Features, Selection, Application Information	DEA-059	Brochures
30A GD AC DISCONNECT OUTLINE DRAWING 30A GD AC DISCONNECT PULLER-TYPE 240V 3HP FUSIBLE RATED METALLIC N3R ENCLOSURE OUTLINE DRAWING	TF30R	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.