



**SKU:** IPC-4/0-6-B

**UPC:**

**Features & Benefits:**

**Description:** KUP-L-Tap Insulation Piercing Copper Connector, Dual Rated, Main Conductor Range 4/0-4, Tap Range 6-14, Tin Plated, UL, CSA, Bag of 1

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Wire Orientation	Parallel

### Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	1.118
Height BX (IN)	3.5
Height (mm)	28.3972
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.252
Weight BX (LB)	1.774
Width (IN)	4
Width BX (IN)	4.875
Width (mm)	101.6

### Material and Finish

Clamping Hardware Finish	Tin
Clamping Hardware Material	Steel
Conductor Material	Aluminum
Connector Finish	Tin
Insulation	Nylon
Material	Copper

### Bolt and Screw Sizes

Clamping Bolt Size	5/16-18
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/16
Wire Binding Torque	156

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366953286

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

## Environment and Temperature

Temperature Rating	90°C
--------------------	------

## Color

Color	Black
-------	-------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 4 Str
Conductor Range AL Stranded (Secondary, tap, load)	6 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	6 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

## Voltage

Voltage Rating	600 V
----------------	-------

## Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	60 Amps
Connector Amperage Rating CU (Derated where applicable)	75 Amps
Conductor Type	Stranded