

15 kV Load Break Feed-Thru Bushing Insert

By Hubbell Power Systems
Catalog # 215FTI

Load Break Feed-Thru Bushing Insert, 200 Amp, 15 kV.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

General

EU RoHS Indicator	No
Type	200Amp Load Break
UPC	096359391548

Dimensions

Dimensions	12.750 in x 9.750 in x 4.375 in
Height	4.375 in
Length	12.750 in
Weight	7.040 lb
Width	9.750 in

Electrical Ratings

AC Withstand Voltage (1 min)	34 kV
Basic Impulse Level	95 kV
Corona Extinction (3pC)	11 kV
Current Rating	200 A
kV Class	15 kV

Logistics

Pallet Quantity	108
Standard Package	1

Product Assets

[Catalogs - Cable Accessories \(C7\)](#)
[Installation Manuals - IS-200FTI_Rev_A_Oct_2016](#)
[Installation Manuals - 15kV & 25kV 200 Amp Feed-thru Inserts](#)
[Installation and Operating Instructions \(IS-200FTI\)](#)
[Sales Drawings - Feed -Thru Insert 15 KV,200A, Loadbreak \(215FTI\)](#)
[SDS - VERSILUBE G661 SILICONE COMPOUND](#)
[Test Documents - ANSI/IEEE Design Test Report - 15kV 200A Loadbreak Separable Connectors \(G11-12-01\)](#)
[Video - 200A Loadbreak Elbow Fault Closure \(VI03045E\)](#)
[Video - Grease Best PRactices \(HPS_CA_UTL_VI_EN_00030\)](#)