

# POWER TECH®

# **Temporary Power Distribution Box**



Power Tech®'s Temporary Power Distribution Box is used by contractors on jobsites (indoor or outdoor) to provide and distribute power from temporary power poles or jobsite generators. Our box is ETL approved for indoor and outdoor use. All outlets have circuit breaker overload protection and all U-Ground outlets are GFCI protected. This offers the highest levels of electrical safety. Multiple 15/20A outlets, and 30A and 50A Twistlocks provide the most popular power outlets that contractors use.

### **FEATURES**

- Power Tech® boxes are used for all types of general construction, roofing, rentals, tradeshows, entertainment events, and wherever portable power is needed.
- We use heavy duty impact resistant steel and special yellow epoxy paint for high visibility, safety, rust resistance and durability.
- Our box is fitted with heavy duty impact and spring-back weatherproof covers which keep out dirt and moisture from the outlets.
- Our GFCI protected duplex receptacles offer open-neutral and reverse-phasing protection for safety.
- These GFCIs offer electrical shock protection by interrupting the circuit when a fault current of 6mA or more is detected.
- Power Tech®'s GFCIs meet the latest UL requirements for continuous self-testing and line/load protection which features an LED light on the receptacle face to indicate your GFCI receptacle is active.
- 7 Individual integrated circuit breakers offer overload protection to each outlet.
- Meets latest ETL & UL 1640 requirements for temporary power, and UL 943 requirements for GFCIs.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# Part number **D18511000YW**

Length **n/a** 

Description

**Power Distribution Box** 

Product line

## **Power Tech® Distribution Box**

Color

Yellow

Gauge/Conductors

n/a

Wire type

n/a

Certifications

cETLus, OSHA

Electrical ratings

50A - 125/250V

Product packaging

Carton

Unit dimensions D x W x H (inches)

15.0 x 18.5 x 13.0

Unit weight (lbs)

24.4

Master carton type

# **Plain corrugated**

Master carton dimensions D x W x H **15.5 x 18.5 x 13.0** 

Master carton weight (lbs)

26

Master carton case quantity

•

Master carton cube (cu. ft.)

2.2

UPC

661899 831689

#### Inlet



50A 125/250V **CS6375** 

### Output/Feed Through



50A 125/250V **CS6369** 

### Outlets



**20A - 125V 5-20R (DUPLEX)\***(GFCI Protected)



30A - 250V L6-30R

\* Accepts 5-15 & 5-20 straight blade plugs