



Representative Image

Catalog No. TLM2412CCUG

Description: 125A CONV LC 24-24CRT N1 W/GRND

UPC No 783164471953

Home > Load Centers > Single Phase - USA

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM2412CCUG features space for 24, 1" breakers, 125 A bus ampere rating, a copper bus, a factory installed ground bar, and a combination/flush enclosure.

Descriptors

Category	Single Phase - USA
----------	--------------------

Specifications

Input/Output Voltage	120/240V ac
Type	Standard
Interrupting Capacity Rating	22
Amperage	125 A
Device type	Main Lug
Enclosure	Indoor Type 1 Enclosure, Surface Mount
Phase	1 Phase
1" Space	24
1/2" Space	0
Feed	Either
Door	Yes
NEMA Rating	NEMA 1
Circuit Breaker Style	Plug-In

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Outline Drawing	DET1023	Application and Technical
Indoor Load Center Section 1 BuyLog: Load centers and circuit breakers	10103091SH18	Drawings-Outline and Dimensional
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.