

# Eaton 3BR4242BC200

Catalog Number: 3BR4242BC200

Eaton BR main breaker loadcenter, No feed-thru lugs, Main circuit breaker, 200 A, L2, Copper, Cover included, NEMA 1, Metallic, 10 kAIC, CC, 42 Circuits, 42 Spaces, Four-wire, Three-phase, #1/0 AWG-250 kcmil Cu/Al, Combination, 208 Y/120, 240 V

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton BR main breaker loadcenter	3BR4242BC200
<b>UPC</b>	<b>Product Length/Depth</b>
786676441155	3.88 in
<b>Product Height</b>	<b>Product Width</b>
34.13 in	14.31 in
<b>Product Weight</b>	<b>Warranty</b>
23 lb	10 year
<b>Certifications</b>	<b>Catalog Notes</b>
UL 67 UL 50	Listed for use as service entrance equipment and shipped with a neutral bonding strap preattached, the maximum rating of the panel is the main breaker rating when used as service entrance equipment.



## Product specifications

### Number of spaces

42

### Special features

No feed-thru lugs

### Interrupt rating

10 kAIC

### Phase

Three-phase

### Wire size

#1/0 AWG-250 kcmil Cu/Al

### Bus material

Copper

### Main circuit breaker

CC

### Enclosure

NEMA 1

### Amperage Rating

200 A

### Mounting

Combination

### Enclosure material

Metallic

### Type

Main circuit breaker

### Cover

Cover included

### Used with

Type BR 1-inch breakers

### NEMA rating

NEMA 1

### Number of wires

4

### Number of circuits

42

## Resources

### Brochures

Loadcenters and Circuit Breakers

### Catalogs

Eaton's Volume 1—Residential and Light Commercial

### Drawings

Dimensional Drawing - BR 1 LOADCENTER, CC MAIN BREAKER, INDOOR NEMA 1, 120/240 VAC, 3 PHASE

### Specifications and datasheets

3-Phase Loadcenter Program

Eaton Specification Sheet - 3BR4242BC200

Voltage rating

208Y/120, 240V

Box size

L2



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)