

Catalog No. THQP230

Description: CIRCUIT BRK 10KA QP 2P 120/240V 30A

UPC No 783164085730

Home > Circuit Breakers > Residential Circuit Breakers > Q Line

THQP breakers are a smaller, smarter solution for today's cost- and quality-conscious contractors and homeowners. Half the width and identical in design in comparison to standard breakers, they allow use of smaller load centers and for maximum savings of space and money. GE is the only manufacturer that gives you this cost advantage without sacrificing flexibility. The THQP230 features 1/2" width, 2 poles, an ampere rating of 30 A, an interrupting rating of 10kAlC, and a voltage rating of 120/240V.

Descriptors	
Category	Q Line
Product Line	Q-Line (Plug-In)
GO Schedule	R5

Specifications		
Interrupting Capacity Rating	10 kAIC	
Voltage	120/240 V	
Trip Style	Non-Interchangeable	
Frame Type	Q-Line	
Amperage	30 A	
System Voltage	120 Vac 120/240 Vac	
Poles	2	
Trip Function	LI	
Continuous Current Rated	Standard	
120 Vac Interrupting Rating	10 KAIC	
120/240 Vac Interrupting Rating	10 KAIC	
Suitable for Reverse Feed	Yes	
Wire Range (Cu/Al)	8-4 kcmil / 8-4 kcmil	
Long Time	Fixed	
Instantaneous	Fixed	
Protective Relays	No	
Current Metering	No	
Special Markings	HACR	
GSA Compliance	Yes	

Classifications	
UL File #	E11592



Created on: 11/21/2021

electrification.us.abb.com

Publications		
Title	Publication No.	Publication Type
PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide	DET1022	Application and
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Q-Line Plug-In MCCB, 100A Frame 1-, 2- Pole, Drawing	DET1023	Technical
1-Page fully dimensioned outline drawing in .pdf format	139C5337-SH1	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

electrification.us.abb.com Created on: 11/21/2021