



**SKU:** ALND-350-12-134

**UPC:** 0783669687552

**Features & Benefits:**

**Description:** Surecrimp Aluminum Compression Lug, Conductor Size 350, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-299
ILSCOs Die Index Number	299
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

### Dimensions

Barrel Length (IN)	2.353
Barrel Length (mm)	59.7662
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	1.145
Height BX (IN)	2
Height (mm)	29.083
Inside Diameter (IN)	0.72
Inside Diameter (mm)	18.288
Length (IN)	6.065
Length (mm)	154.051
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	1.105
Outside Diameter (mm)	28.067
Strip Length (mm)	61.3537
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.385
Tang Thickness (mm)	9.779

Tang Width (IN)	1.516
Tang Width (mm)	38.5064
Weight (LB)	0.28
Weight BX (LB)	1.547
Width (IN)	1.516
Width BX (IN)	6.188
Width (mm)	38.5064

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	350 kcmil - 3/0 Str
Flex Conductor Range	NA

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366968755

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
Color Code	Brown

### Voltage

Voltage Rating	35 kV
----------------	-------