


CATALOG NUMBER	[A]	[B]	[C]	[D]
200LUGB1	2.88IN [73.15MM]	1.90IN [48.26MM]	.225IN [5.72MM]	.625IN [15.88MM]
200LUGB2			.285IN [7.24MM]	.625IN [15.88MM]
200LUGB3			.310IN [7.87MM]	.625IN [15.88MM]
200LUGB4			.360IN [9.14MM]	.625IN [15.88MM]
200LUGB5			.395IN [10.03MM]	.625IN [15.88MM]
200LUGB6			.440IN [11.18MM]	.625IN [15.88MM]
200LUGB7	2.75IN [69.85MM]	1.69IN [42.88MM]	.495IN [12.57MM]	.780IN [19.81MM]
200LUGB8			.550IN [13.97MM]	.780IN [19.81MM]

CATALOG NUMBER	CONDUCTOR SIZE (COPPER OR ALUMINUM)	
	STANDARD OR COMPRESSED	SOLID OR COMPACTED
200LUGB1	6	4
200LUGB2	4	2
200LUGB3	2	1
200LUGB4	1	1/0
200LUGB5	1/0	2/0
200LUGB6	2/0	3/0
200LUGB7	3/0	4/0
200LUGB8	4/0	--

<p>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</p>			HUBBELL® POWER SYSTEMS	
	TITLE 200 AMP, 15/25 KV LONG, BIMETAL CONNECTOR			
REV DATE 04/25/07	SIZE S	DWG NO. --	CAT / PART / ASSY NO. 200LUGBX	REV 1
DO NOT SCALE THIS DRAWING		DRN BY JVR	DATE 11/21/06	SHEET 1 OF 1