



SKU: ASN-3/0

UPC: 0783669184785

Features & Benefits:

Description: Surecrimp Aluminum Compression Sleeve, Conductor Size 3/0, Tin Plated, UL, CSA

Specs

Dimensions

Height (IN)	0.761
Height BX (IN)	2.25
Height (mm)	19.3294
Inside Diameter (IN)	0.495
Inside Diameter (mm)	12.573
Length (IN)	2.71
Length (mm)	68.834
Outside Diameter (IN)	0.761
Outside Diameter (mm)	19.3294
Weight (LB)	0.069
Weight BX (LB)	0.7807
Width (IN)	0.761
Width BX (IN)	5
Width (mm)	19.3294

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Standard
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	297
Number of Conductors	1

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	3/0 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	3/0 Str - 1 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin

Material

Aluminum

Additional Technical Specifications

Conductor Type

Stranded

General

Bag Quantity

1

Carton Quantity Description

STD PACK QTY 10

Dual Rated

Yes

NEMA Code

S-588-1

UPC Code

78366918478

Testing Standards

CSA File Number

LR-29601

CSA Standard

C22.2 No. 65-03

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

453G

UL / CULUS Specification

UL 486A/B Listed

UL File Number

E6207

Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Ruby

Voltage

Voltage Rating

35 kV