



Catalog No. TL30420C

Description: MLO 200A 30CRT 3P4W 208Y/120V COMBO

UPC No 783164189926

Home > Load Centers > Three Phase - USA

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL30420C features space for 30, 1" breakers, 3 phases, a 200 A bus ampere rating, and a combination/flush enclosure.

Descriptors

Category	Three Phase - USA
GO Schedule	R7

Specifications

Input/Output Voltage	208Y/120V ac
Type	Standard
Interrupting Capacity Rating	65
Amperage	200 A
Device type	Main Lug
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	3 Phase
Socket Type	0
1" Space	30
1/2" Space	0
Feed	Either
Door	Yes
GSA Compliance	Yes
NEMA Rating	NEMA 1
Circuit Breaker Style	Plug-In

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Indoor Load Center 1 page outline drawing in pdf format.	DET1023 10103091-SH21	Application and Technical Drawings-Outline and Dimensional
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.