



**PIGTAIL:**  
 WIRE: #12 AWG STRANDED, 10-1/2" LONG, GREEN INSULATED, U.L. LISTED, 600 VOLT MAX;  
 EXTRA-GRIP RING TERMINAL, 16/12 AWG BRASS;  
 #10-32 X 3/8" GROUND SCREW W/COMBO HEX WASHER HEAD (SLOTTED, #2 PHILLIPS AND ROBERTSON)

**LIST OF PARTS**

DESCRIPTION	MATERIAL	FINISH
SPACER	STEEL	GALVANIZED
SIDE	STEEL	GALVANIZED
FARSIDE SUPPORT	STEEL	GALVANIZED
STUD BRACKET	STEEL	GALVANIZED
FASTENERS	STEEL	GALVANIZED
PIGTAIL	INSULATED STRANDED COPPER	N/A

189H CUS

SYM.	REVISION DESCRIPTION	APP	DATE
	INITIAL RELEASE	RMV	11-20-17

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE

TITLE:  
**4" SQ BOX W/ FARSIDE SUPPORT, STUD BRACKET, & GROUND**

TOLERANCE UNLESS OTHERWISE SPECIFIED

**RACO**  
 South Bend, Indiana

.XX DECIMAL ±.015  
 .XXX DECIMAL ±.005  
 ANGLE ±2°

DRAWN BY:	RMV	SCALE:	1:3
APP. BY:	N.S.		
DATE:	11-20-17		

189H  
 DIMENSION SHEET FOR CAT. NO.

SIZE:  
**A**

11in\*17in

- NOTES:  
 1. ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS]  
 2. BOX VOLUME: 21.0 IN<sup>3</sup> [344.1 CM<sup>3</sup>]  
 3. UL LISTED

KNOCKOUTS		
TRADE SIZE	LOCATION	QTY.
(1/2"-3/4") TKO®	A, B, C, D	1
1/2" KO	A, B, C, D, E	2
(1/2"-3/4") TKO®	E	2