



Catalog No. R011C010U

Description: 100A SURFACE MTRD 20/20GFCI

UPC No 784567205527

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Temporary Power
----------	-----------------

Specifications

Mounting	Surface
Heads	1
Metering	Ringless
Receptacles	(2) 5-20R2GFCI
Feed	Underground
AIC	10,000
Amps	100.0 A
Cabinet Size	9 X 30U
Circuit Protection	Yes
Hub Provision	No
Installed Breaker	(2) CB120
Load Center	LC33N1
Loop Feed	Yes
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	21.0 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
Storm Season Brochure This brochure highlights the most popular products sold during storm season.	MET1005	Brochures
Storm Season Brochure This brochure highlights the most popular products sold during storm season.	005	Brochures
Temporary Power Brochure 6 pages. MET-019 Rev. B.	MET-019A	Brochures
Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Outline Drawing Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Bottom 120V 1PH G90 N3R Outline Drawing	R011C010U	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.