



Catalog No. TLM1212RCU

Description: FLD CNVRTB 125A 12CRK 22K IC 3R

UPC No 783164112931

Home > Load Centers > Single Phase - USA

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM1212RCU features space for 12, 1" breakers, a 125 A bus ampere rating, a copper bus, and an outdoor suitable enclosure.

Descriptors

Category	Single Phase - USA
GO Schedule	RD

Specifications

Input/Output Voltage	120/240V ac
Type	Standard
Interrupting Capacity Rating	65
Amperage	125 A
Device type	Main Lug
Enclosure	Outdoor Type 3R Enclosure
Phase	1 Phase
Socket Type	0
1" Space	12
1/2" Space	24
Feed	Either
Door	Yes
GSA Compliance	Yes
NEMA Rating	NEMA 3R
Circuit Breaker Style	Plug-In

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers essories and options list. Only available on-line.	DET1023	Application and Technical
Outdoor Load Center 1 page outline drawing in pdf format.	10103091-SH1	Drawings-Outline and Dimensional
PowerMark Gold* Load Centers: 100-125 Amps, 12/22/24 Circuits, Outdoor 2 pages.	DET-800	Brochures
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.