



**SKU:** ALNS-600-12

**UPC:** 0783669687804

**Features & Benefits:**

**Description:** Surecrimp Aluminum Compression Lug, Conductor Size 600, 1 Hole, 1/2in Bolt Size, Long Barrel, No Sight Window, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-473
ILSCOs Die Index Number	473
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

### Dimensions

Barrel Length (IN)	2.685
Barrel Length (mm)	68.199
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	1.485
Height BX (IN)	2.25
Height (mm)	37.719
Inside Diameter (IN)	0.92
Inside Diameter (mm)	23.368
Length (IN)	5.12
Length (mm)	130.048
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	1.44
Outside Diameter (mm)	36.576
Strip Length (mm)	69.7865
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.52
Tang Thickness (mm)	13.208

Tang Width (IN)	1.965
Tang Width (mm)	49.911
Weight (LB)	0.221
Weight BX (LB)	0.401
Width (IN)	1.965
Width BX (IN)	5
Width (mm)	49.911

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	600 kcmil
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	600 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	600 kcmil - 250 kcmil
Flex Conductor Range	NA

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366968780

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating

90°C

**Color**

Color

Silver

Color Code

Black

**Voltage**

Voltage Rating

35 kV